



## SHREDDERS-AND-CHIPPERS

## VERSION | R280TN



## BASIC EQUIPMENT

- ROTOR | Blades + Hammers
- Sharpenable blades (hardened steel)
- Mobile reversible hammers (hardened steel)
- Fixed removable refining screen
- Hydraulic feeding roller with adjustable speed and rotation direction
- Feeding conveyor belt in steel with adjustable speed and rotation direction
- Rotary ejection pipe with adjustable discharge distance
- Large and handy hopper
- Lubrication system for bearings
- OBS - On Board System (Multifunctional control system with Nostress)
- Belt transmission with gearbox
- Rotary fifth-wheel coupling
- Homologated road trailer at reduced speed + Fixed drawbar with towing eye

## ACCESSORIES

- Ejection pipe extension (400 mm)
- CE marked cardan shaft with freewheel

## CUTTING SYSTEM

Blades (hardened steel)	N°	4
Hammers (hardened steel)	N°	20
Counter-blade	N°	1

## FEATURES

Hourly capacity	m <sup>3</sup> /h*	13 - 18
Throat opening	mm	270 x 150
To shred - Ø max.*	mm	150

## MOTIVE POWER

Power	hp/kW	≥ 40 / 29,5
Power source		Towed by tractor
Engine/motor		Tractor
Fuel consumption	liters/h	/

## SPECIFICATIONS

Length	mm	3590/2690
Width	mm	1540/2525
Height	mm	2390
Discharge height	mm	2390
Introduction height	mm	810
Hopper size	mm	1205 x 870
Weight: NET	kg	720

\* Input material - Data depending on the kind of material and working conditions.

**TERMS**

Product origin	Made in Italy
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	<a href="https://echa.europa.eu/it/scip-database">https://echa.europa.eu/it/scip-database</a>

The products are subject to technical evolution and this website may not be fully updated.  
The data in the tables, the photos and pictures have to be considered informative and not binding.