




## SHREDDERS-AND-CHIPPERS

## VERSION | R185TRIN



## BASIC EQUIPMENT

- DISC | Blades+Counter-blade
- Sharpenable blades (hardened steel)
- Mobile reversible hammers (hardened steel)
- Adjustable counter-blade
- Mobile refining screen
- Rotary ejection pipe with adjustable discharge distance
- Lubrication system for bearings
- Hydraulic feeding roller with adjustable speed and rotation direction
- Nostress control
- Transmission with gearbox and elastic joint
- Three-point linkage for tractor - Category 1

## ACCESSORIES

- Ejection pipe extension (400 mm)
- CE marked cardan shaft with freewheel

## CUTTING SYSTEM

Blades (hardened steel)	N°	2
Hammers (hardened steel)	N°	10
Counter-blade	N°	1

## FEATURES

Hourly capacity	m <sup>3</sup> /h*	6 - 7
Throat opening	mm	160 x 90
To shred - Ø max.*	mm	90

## MOTIVE POWER

Power	hp/kW	≥ 15 / 11
Power source		Three-point linkage for tractor / LONGITUDINAL MACHINE
Engine/motor		Tractor
Fuel consumption	liters/h	/

## SPECIFICATIONS

Length	mm	2350
Width	mm	1000
Height	mm	1750
Discharge height	mm	1750
Introduction height	mm	1000
Hopper size	mm	700 x 725
Weight: NET	kg	300

\* Input material - Data depending on the kind of material and working conditions.



TERMS	
Product origin	Made in Italy
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	<a href="https://echa.europa.eu/it/scip-database">https://echa.europa.eu/it/scip-database</a>

The products are subject to technical evolution and this website may not be fully updated.  
The data in the tables, the photos and pictures have to be considered informative and not binding.