



## SHREDDERS-AND-CHIPPERS

## VERSION | R240BHHP210N-M



## BASIC EQUIPMENT

- ROTOR | Hammers
- Mobile reversible hammers (hardened steel)
- Fixed removable refining screen
- Hydraulic feeding roller with adjustable speed and rotation direction
- Rotary ejection pipe with adjustable discharge distance
- Large and handy hopper
- Lubrication system for bearings
- OBS - On Board System (Multifunctional control system with Nostress)
- Belt transmission with hydrodynamic joint
- Homologated road trailer + Fixed drawbar with ball hitch coupling
- HONDA GX630
- Electric start

## ACCESSORIES

- Ejection pipe extension (400 mm)

## CUTTING SYSTEM

Blades (hardened steel)	N°	/
Hammers (hardened steel)	N°	33
Counter-blade	N°	1

## FEATURES

Hourly capacity	m <sup>3</sup> /h*	7 - 10
Throat opening	mm	286 x 90
To shred - Ø max.*	mm	90

## MOTIVE POWER

Power	hp/kW	21 / 15,5
Power source		Petrol
Engine/motor		HONDA GX630
Fuel consumption	liters/h	4,8

## SPECIFICATIONS

Length	mm	3080
Width	mm	1310
Height	mm	1900
Discharge height	mm	1900
Introduction height	mm	1015
Hopper size	mm	700 x 660
Weight: NET	kg	515

\* Input material - Data depending on the kind of material and working conditions.

**TERMS**

Product origin	Made in Italy
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	<a href="https://echa.europa.eu/it/scip-database">https://echa.europa.eu/it/scip-database</a>

The products are subject to technical evolution and this website may not be fully updated.  
The data in the tables, the photos and pictures have to be considered informative and not binding.