

SHREDDERS-AND-CHIPPERS

VERSION | R185BHHP13AERIN



- 6			_	_	 ш	пл		VΤ
В	V A		-		 ı	W	13/	
	<i>I</i> =	_,	 	u		_		и .

- DISC | Blades+Counter-blade
- Sharpenable blades (hardened steel)
- Mobile reversible hammers (hardened steel)
- Adjustable counter-blade
- Mobile refining screen
- Rotary ejection pipe with adjustable discharge distance
- Lubrication system for bearings
- Hydraulic feeding roller with adjustable speed and rotation direction
- Nostress control
- Belt transmission with clutch
- 2 pneumatic wheels + drawbar with jockey wheel (non-road towing)
- HONDA GX390
- Electric start

ACCESSORIES

- Ejection pipe extension (400 mm)
- Third pneumatic wheel kit

TTIN			
		V S I F	- 11/1
 	143		

Blades (hardened steel)	N°	2
Hammers (hardened steel)	N°	10
Counter-blade	N°	1

FEATURES

Hourly capacity	m³/h*	6 - 7
Throat opening	mm	160 x 90
To shred - 1 may *	mm	an

MOTIVE POWER

Power	hp/kW	13 / 9,6			
Power source		Petrol			
Engine/motor		HONDA GX390			
Fuel consumption	liters/h	2,8			

SPECIFICATIONS

SI CONTRACTIONS					
Length	mm	2900			
Width	mm	1000			
Height	mm	1750			
Discharge height	mm	1750			
Introduction height	mm	1000			
Hopper size	mm	700 x 725			
Weight: NET	kg	340			

^{*} Input material - Data depending on the kind of material and working conditions.



TERMS				
Product origin	Made in Italy			
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.			
Delivery - Original spare parts	Usually available, 45 days max. (from order date)			
Identification - SCIP number (link)	https://echa.europa.eu/it/scip-database			

The products are subject to technical evolution and this website may not be fully updated. The data in the tables, the photos and pictures have to be considered informative and not binding.