



SHREDDERS-AND-CHIPPERS

VERSION | R280BH250TRON-M



BASIC EQUIPMENT

- ROTOR | Hammers
- Mobile reversible hammers (hardened steel)
- Fixed removable refining screen
- Hydraulic feeding roller with adjustable speed and rotation direction
- Feeding conveyor belt in steel with adjustable speed and rotation direction
- Rotary ejection pipe with adjustable discharge distance
- Large and handy hopper
- Lubrication system for bearings
- OBS - On Board System (Multifunctional control system with Nostress)
- Belt transmission with hydrodynamic joint
- Homologated road trailer + Adjustable drawbar with towing eye
- HONDA iGX800
- Electric start

ACCESSORIES

- Ejection pipe extension (400 mm)

CUTTING SYSTEM

Blades (hardened steel)	N°	/
Hammers (hardened steel)	N°	24
Counter-blade	N°	1

FEATURES

Hourly capacity	m ³ /h*	13 - 18
Throat opening	mm	270 x 150
To shred - Ø max.*	mm	150

MOTIVE POWER

Power	hp/kW	25 / 18,5
Power source		Petrol
Engine/motor		HONDA iGX800
Fuel consumption	liters/h	5,5

SPECIFICATIONS

Length	mm	3470
Width	mm	1470
Height	mm	2280
Discharge height	mm	2280
Introduction height	mm	700
Hopper size	mm	1205 x 870
Weight: NET	kg	700

* Input material - Data depending on the kind of material and working conditions.



TERMS	
Product origin	Made in Italy
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	https://echa.europa.eu/it/scip-database

The products are subject to technical evolution and this website may not be fully updated.
The data in the tables, the photos and pictures have to be considered informative and not binding.