

SHREDDERS-AND-CHIPPERS

VERSION | R340DL560TRON-M



BASIC EQUIPMENT

- ROTOR | Hammers
- Mobile reversible hammers (hardened steel)
- Fixed removable refining screen
- Hydraulic feeding roller with adjustable speed and rotation direction
- Feeding conveyor belt in steel with adjustable speed and rotation direction
- Rotary ejection pipe with adjustable discharge distance
- Large and handy hopper
- Lubrication system for bearings
- OBS On Board System (Multifunctional control system with Nostress)
- Belt transmission with hydrodynamic joint
- Homologated road trailer + Adjustable drawbar with towing eye
- KOHLER KDI1903TCR
- Electric start

ACCESSORIES	-
	9)

ACCESSORIES		
CUTTING SYSTEM		
Blades (hardened steel)	N°	/
Hammers (hardened steel)	N°	40
Counter-blade	N°	1
FEATURES		
Hourly capacity	m³/h*	25 - 30
Throat opening	mm	390 x 180
To shred - Ø max.*	mm	180
MOTIVE POWER		
Power	hp/kW	56 / 42
Power source		Diesel
Engine/motor		KOHLER KDI1903TCR
Fuel consumption	liters/h	9,6
SPECIFICATIONS		
Length	mm	4425
Width	mm	1570
Height	mm	2535
Discharge height	mm	2535
Introduction height	mm	725
Hopper size	mm	1360 x 880
Weight: NET	kg	1655

^{*} Input material - Data depending on the kind of material and working conditions.



TERMS	
Product origin	Made in Italy
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	https://echa.europa.eu/it/scip-database

The products are subject to technical evolution and this website may not be fully updated. The data in the tables, the photos and pictures have to be considered informative and not binding.